

NKCR2
Component - Auxiliary Devices

April 28, 1998

IDEC IZUMI CORP
7-31 NISHIMIYAHARA 1-CHOME YODOGAWA-KU, OSAKA
532-0004 JAPAN

E68961 (S)
(A card)

Magnetically operated switches, Cat. No. RV3S followed by B or G, followed by DC3V through DC24V incl.

Pilot lights, Cat. Nos. SLC30N f/b-01 to -10, f/b-01 to -20, f/b DD, DHM, DW, DF or DS, f/b-1, -2, -3, -6 or -8, may be followed by NKCR2; Models SLC40N, f/b-01 to -07, f/b-01 to -15, f/b DD, DHM, DW, DF or DE, f/b-1, -2, -3, -6 or -8, may be followed by NKCR2.

Magnetically operated switches, for use in electronic data processing equipment or office appliance and business equipment (nonindustrial), Type RV3S, may be followed by B, G, 3B or 3G, followed by 05S thru 24S incl: Relay socket, Type RV9Z-S01.

LED illuminated miniature pilot lights, AP Series; Models AP1M, AP2M, AP6M, AP8M; **Transformer**, Models AP2, APG.

Enable switch, Cat. No. HE1B-M1.

Reports: May 26, 1992; September 15, 1992; August 25, 1994; February 8, 1995; April 23, 1998.

Replaces E68961A dated January 30, 1995.

365882001

Underwriters Laboratories Inc.®

(Cont. on B card)

D1I/0212617
166

