

DESCRIPTION

The Halo ML56 LED Downlighting System is a series of modular LED Light Modules for use with dedicated 5" or 6" ML56 LED trims. The ML56 system is suitable for new construction, remodel and retrofit installation.

The ML56 light modules and LED trims fit 5" or 6" housings including the Halo LED 5" H550 and 6" H750 Series for new construction and remodel. And for retrofit of existing housings the ML56 Series fits the Halo 5" H5 and 6" H7 series, All-Pro 5" ET/EI500 and 6" ET/EI700 series, and other compatible 5" and 6" housings. In addition, for shallow ceiling housings the ML56 system offers shallow trims that allow installation in Halo 5" H25 and 6" H27 series, All-Pro 6" EI2700 series, and other shallow housings.

ML56 Light Module System is offered in 600 Series and 900 Series, 80CRI or 90CRI, and four color temperatures 2700K, 3000K, 3500K, 4000K.

ML56 Light Modules are universal voltage 120V – 277V with integral LED drivers that are dimmable at 120V. The ML56 lens provides uniform illumination and wet location listing with reflector and baffle trims. Halo ML56 Series offers high performance LED downlighting in a flexible modular selection.

SPECIFICATION FEATURES

MECHANICAL

Light Module

Module includes LED package, LED driver, heat sink, and lens

- Durable die-cast aluminum construction.
- Heat sink designed to conduct heat away from the LED keeping the junction temperatures below specified maximums, even when installed in insulated ceiling environments

Lens

- Impact-resistant polycarbonate
- Convex form for lamp-like appearance
- High lumen transmission
- Diffusing for even illumination

MOUNTING

- Light Modules attach to reflector and baffle trims via locking tabs, and attach to eyeballs via keyed twist-to-lock mating bosses
- The complete light module and trim assembly installs into housings with precision formed torsion springs located on the trim
- Friction Blade mounting is an alternate option using the accessory 6" Friction Blade Kit model ML56CLIP (order separately). Friction blades provide alternative to torsion springs for retrofit in 6" housings without torsion mounting tabs. The stainless steel friction blades allow the ML56 to be installed in a wider range of housings, and allow rotation in the housing aperture (360 degrees).

Housing Compatibility

A complete ML56 system includes a LED Light Module, LED trim, and a compatible housing (new construction, remodel, or existing retrofit). Housing compatibility in the ML56 System is determined by the ML56 trim dimensions. ML56 trims are available in 5" and 6" aperture (5" = 59xx series and 6" = 69xx series trims). Refer to Housing – Trim Compatibility in this document.

LED

- 600 Series = 600 design lumens
- 600 Series 80CRI = 408 - 708 delivered lumens (Design lumens typical for respective series light modules. Delivered lumens vary depending upon CRI, color temperature, and trim finish selected.)
- Color Temperature options: 2700K, 3000K, 3500K, 4000K
- CRI: 80
- Lumen Maintenance: L70/B50 70% lumens / 50,000 hours
- Efficacy: up to 78 Lumens per Watt
- LED is a chip on board design consisting of a multiple LED package to create one virtual light source for a productive "cone of light"

COLOR SPECIFICATION & QUALITY STANDARDS

- Halo employs a tight chromaticity specification to ensure LED color uniformity, sustainable Color Rendering Index (CRI) and Correlated Color Temperature (CCT) consistency over the useful life of the LED

Catalog #		Type
Project		
Comments		Date
Prepared by		



ML56 LED System

600 Series / 80 CRI

ML5606827

ML5606830

ML5606835

ML5606840

5-Inch and 6-Inch
600 Lumen LED
Light Module for
New Construction,
Remodel and Retrofit

For use with 59x and 69x
Series Trims

FOR USE IN
INSULATED CEILING
AND NON-INSULATED
CEILING RATED
HOUSINGS

HIGH EFFICACY LED
WITH INTEGRAL
DRIVER - DIMMABLE

- Halo LED chromaticity specification of 3 SDCM initial and 5 SDCM life exceeds ENERGY STAR® color standards per ANSI C78.377-2008.
- Every Halo LED Light Module is quality tested and performance measured, and then serialized in a permanent record to register lumens, wattage, CRI and CCT.
- Halo LED's serialized testing and measurement process ensures color and lumen consistency on a per-unit basis, and also validates long-term product consistency over time
- Halo ML56 LED Light Modules include lumen, CRI, and CCT designations in the model number
- Example: ML5606830
56 06 8 30
56 = 5" / 6" aperture series
06 = 600 lumen
8 = >80 CRI
30 = 3000K nominal CCT

ELECTRICAL POWER CONNECTIONS

- LED connector is a non-screw base luminaire disconnect offering easy installation with the matching Halo 5" H550 Series and 6" H750 Series housings (housing selected depends upon LED trim 5" or 6").
- LED Connector meets California Title-24 high-efficacy luminaire requirement for a non-screw base socket, and where required to qualify as a high-efficacy luminaire.
- The included E26 medium screw-base Edison adapter provides easy retrofit of incandescent housings (see Housing Compatibility).

ENERGY DATA

ML56 600/80 Series

(Values at non-dimming line voltage)

Minimum Starting Temp: -30°C (-22°F)

EMI/RFI: FCC Title 47 CFR, Part 18,

(Consumer)

Sound Rating: Class A

Input Voltage: UNV 120V-277V

Power Factor: >0.95 @ 120V and >0.9 @ 277V

Input Frequency: 50/60Hz

THD: <20%

Max. Rated Wattage: 10W

Input Power: 9.0W

Input Current at 120V: 0.15A

Input Current at 277V: 0.08A

Driver Compliance: UL8750, Class II rated


Maximum IC (Insulated Ceiling) Ambient

Continuous Operating Temperature:

25°C (77°F)


Maximum Non-IC Ambient Continuous

Operating Temperature: 40°C (104°F)




ML5606827

5" or 6" LED 600 Series
Light Module, 80CRI / 2700K




ML5606830

5" or 6" LED 600 Series
Light Module, 80CRI / 3000K



ML5606835

5" or 6" LED 600 Series
Light Module, 80CRI / 3500K



ML5606840

5" or 6" LED 600 Series
Light Module, 80CRI / 4000K



ML56 LED System

600 Series / 80 CRI

ML5606827

ML5606830

ML5606835

ML5606840

5-Inch and 6-Inch
600 Lumen LED
Light Module for
New Construction,
Remodel and Retrofit

For use with 59x and 69x
Series Trims

FOR USE IN
INSULATED CEILING
AND NON-INSULATED
CEILING RATED
HOUSINGS

HIGH EFFICACY LED
WITH INTEGRAL
DRIVER - DIMMABLE

SPECIFICATION FEATURES continued

Ground Connection

- Separate grounding cable included on the module for attachment to the housing during installation.

LED Driver

- Driver is universal voltage 120V-277V, and may be controlled from a switch in this range of main inputs (switchable at 120V, 220V, 230V, 240V, and 277V)
- Driver is dimmable at 120V operation when connected to a compatible dimmer.
- Driver is a high efficiency, electronic power supply providing DC power to the LED.
- Driver meets FCC EMI/RFI Consumer Level limits on 120V main inputs, and is suitable for use in residential and commercial installations.
- Driver features high power factor, low THD, and has integral thermal protection in the event of over temperature or internal failure.
- Driver is replaceable, if replacement should be required.

Dimming

- Halo ML56 LED System is designed for dimming capability to 15% in normal operation with standard 120V electronic low voltage, LED-Rated, and many incandescent dimmers. The ML56 Light Module has dimming capability to 5% with select dimmers with low end trim adjustment. (Consult dimmer manufacturer for dimmer compatibility and details. Note, some dimmers require a neutral in the wallbox.)

Warranty

- Cooper Lighting provides a (5) five year limited warranty on the Halo ML56 LED Light Module.

LED Module in New or Retrofit Existing Construction – Housings other than Halo or All-Pro

- If used in recessed housings other than Halo or All-Pro the Cooper Lighting 5-year limited warranty applies to the LED Light Module and Trim only.
- As with any electrical installation, a qualified electrician must ensure compatibility of use with a particular housing; this includes all applicable national and local electrical and building codes. Installer is responsible to properly and securely retain the LED Module and LED Trim in the housing at time of installation.

COMPLIANCE Labels

- UL/cUL Listed 1598 Luminaire (Halo and All-Pro housings)
- CE Marking - "Conformité Européenne" conformity with the *Council of European Communities Directives*, meeting internationally recognized compliance when used with H550 and H750 LED housings
- UL/cUL Listed for Damp Location
- UL/cUL Listed for Wet Location (Protected Ceiling) with baffle and reflector trims
- IP66 rated with baffle and reflector trims
- RoHS Compliant
- May be installed in IC housings in direct contact with air permeable insulation and combustible material
- UL Classified when used in retrofit with listed housings (See Housing Compatibility)

Qualification

- ENERGY STAR® qualified as registered in the "ENERGY STAR® Qualified Products List"
- May be used for State of California Title 24 high efficacy LED luminaire compliance, as registered in the State of California Energy Commission "Appliance Database"
- May be used for International Energy Conservation Code (IECC) high efficacy luminaire compliance
- May be used for Washington State Energy Code (WSEC) high efficacy luminaire compliance

AIR-TITE™



Certified under ASTM-E283 to meet insulated ceiling and restricted air-flow requirements such as:

- International Energy Conservation Code (IECC)
- Washington State Energy Code (WSEC)
- New York State Energy Conservation Construction Code (NY-ECCC)
- State of California Title 24 "Recessed Luminaires in Insulated Ceilings"



Qualified and compliant. Refer to ENERGY STAR® Qualified Products List and CEC (T24) Appliance Database for listings.

DIMENSIONS



ORDERING INFORMATION

SAMPLE NUMBER: ML5606830 593WB

Order LED Module and trim separately.

A complete system also includes a compatible housing (new construction, remodel, or existing retrofit). Housing compatibility in the ML56 System is determined by the ML56 trim dimensions. ML56 trims are available in 5" and 6" aperture (5" = 59xx series and 6" = 69xx series trims). Refer to *Housing – Trim Compatibility* in this document.

ML56 LED Light Modules 600 Series / 80 CRI	ML56 LED 5" and 6" Trims	ML56 System Accessories
<p>ML5606827= 5"/6" LED Retrofit Downlight Light Module, 600 lumen, 80CRI, 2700K</p> <p>ML5606830= 5"/6" LED Retrofit Downlight Light Module, 600 lumen, 80CRI, 3000K</p> <p>ML5606835= 5"/6" LED Retrofit Downlight Light Module, 600 lumen, 80CRI, 3500K</p> <p>ML5606840= 5"/6" LED Retrofit Downlight Light Module, 600 lumen, 80CRI, 4000K</p>	<p>590 Series - 5" LED Trims</p> <p>591WB=5" LED Trim, Polymer "Dead-Front", Shallow White Baffle & Flange – Shallow and Standard housings (For use with 600 Series LED Light Modules only)</p> <p>592SC=5" LED Trim, Specular Reflector & White Flange</p> <p>592H=5" LED Trim, Haze Reflector & White Flange</p> <p>592W=5" LED Trim, White Reflector & Flange</p> <p>593WB=5" LED Trim, White Micro-Step Baffle & Flange</p> <p>593BB=5" LED Trim, Black Micro-Step Baffle & White Flange</p> <p>593SNB=5" LED Trim, Satin Nickel Micro-Step Baffle & Flange</p> <p>593TBZB=5" LED Trim, Tuscan Bronze Micro-Step Baffle & Flange</p> <p>594WB=5" LED Directional Trim, White Eyeball, Baffle & Flange – Shallow and Standard Housings</p> <p>594SNB=5" LED Directional Trim, Satin Nickel Eyeball, Baffle & Flange – Shallow and Standard Housings</p> <p>594TBZB=5" LED Directional Trim, Tuscan Bronze Eyeball, Baffle & Flange – Shallow and Standard Housings</p> <p>595WW=5" LED Trim, Wall Wash - Specular Reflector, Repositionable Specular Kick Reflector, White Flange</p> <p>596WB=5" LED Trim, White Shallow Baffle & Flange – Shallow and Standard Housings</p> <p>690 Series - 6" LED Trims</p> <p>691WB=6" LED Trim, Polymer "Dead-Front", White Shallow Baffle & Flange – Shallow and Standard housings (For use with 600 Series LED Light Modules only)</p> <p>692SC=6" LED Trim, Specular Reflector & White Flange</p> <p>692H=6" LED Trim, Haze Reflector & White Flange</p> <p>692W=6" LED Trim, White Reflector & Flange</p> <p>693WB=6" LED Trim, White Micro-Step Baffle & Flange</p> <p>693BB=6" LED Trim, Black Micro-Step Baffle & White Flange</p> <p>693SNB=6" LED Trim, Satin Nickel Micro-Step Baffle & Flange</p> <p>693TBZB=6" LED Trim, Tuscan Bronze Micro-Step Baffle & Flange</p> <p>694WB=6" LED Directional Trim, White Eyeball, Baffle & Flange – Shallow and Standard Housings</p> <p>694SNB=6" LED Directional Trim, Satin Nickel Eyeball, Baffle & Flange – Shallow and Standard Housings</p> <p>694TBZB=6" LED Directional Trim, Tuscan Bronze Eyeball, Baffle & Flange – Shallow and Standard Housings</p> <p>695WW=6" LED Trim, Wall Wash - Specular Reflector, Repositionable Specular Kick Reflector, White Flange</p> <p>696WB=6" LED Trim, White Shallow Baffle & Flange – for use with Shallow and Standard Housings</p>	<p>ML56CLIP=Friction Clip Mounting Kit - For retrofitting non-torsion spring housings, 6" clips*</p> <p>WW595SC=5" Wall Wash Insert - Kick Reflector for 595WW (1-included with trim) Double or Corner Wall Wash**</p> <p>WW695SC=6" Wall Wash Insert - Kick Reflector for 695WW (1-included with trim) Double or Corner Wall Wash**</p> <p>TRM590WH= 5" LED Oversize Trim Ring for use with 59" series trims, White 6.3" I.D., 7.5" O.D. Ring slips over LED trim. Inset design allows 5" trim to fit into oversize ring for an even trim surface</p> <p>TRM690WH= 6" LED Oversize Trim Ring for use with 69" series trims, White 6.9" I.D., 9.5" O.D. Ring slips over LED trim. Inset design allows 6" trim to fit into oversize ring for an even trim surface</p> <p>*ML56CLIP is compatible with 6" baffle and reflector trims only (691, 692, 693, 695, 696 series). For eyeball trim (694 series) use ML7RAB retrofit adapter band.</p> <p>**Wall Wash Trims 595WW and 695WW Feature an exclusive Repositionable Kick Reflector for fine-tuning adjustment of the wall wash effect. The WW595SC and WW695SC are Repositionable Kick Reflectors sold separately for addition to the Wall Wash Trim when a double or corner wall wash is needed, or for replacement of original kick reflector included with the trim.</p>

LIGHTING FACTS

ML5606827



ML5606830



ML5606835



ML5606840



HOUSING – TRIM COMPATIBILITY

Housing compatibility in the ML56 System is determined by the ML56 trim dimensions. ML56 trims are available in 5" and 6" aperture (5" = 59xx series and 6" = 69xx series trims). Refer to **ML56 TRIMS** in this document. (Note "X" in the trim model number denotes finish code.)

Halo and All-Pro UL Listed Compatibility
6" Trims: 691X, 692X, 693X, 694X, 695X, 696X

(Note shallow housings for use with 691X, 694X, 696X trims only)

HALO - LED Housings with LED luminaire connector - high-efficacy compliant		
HALO	Catalog Number	Description
	Standard Housings	
	H750ICAT	6" LED, Insulated Ceiling, AIR-TITE, New Construction Housing
	H750RICAT	6" LED, Insulated Ceiling, AIR-TITE, Remodel Housing
	H750T	6" LED, Non-IC, AIR-TITE, New Construction Housing
	H750TCP	6" LED, Non-IC, New Construction/Remodel Chicago Plenum Housing
	H750TD010	6" LED, Non-IC, AIR-TITE, New Construction Housing
	H750RTD010	6" LED, Non-IC, AIR-TITE, Remodel Housing
	H750TCPD010	6" LED, Non-IC, New Construction/Remodel Chicago Plenum Housing
	H750RINTD010	6" LED, Non-IC, AIR-TITE, Remodel Housing (International CE Mark and UL/cUL Listed)
	Shallow Housings	
	H2750ICAT	6" LED, Shallow, Insulated Ceiling, AIR-TITE, New Constr. (use with 691X, 694X, 696X trims only)

HALO and All-Pro - Incandescent E26 Screwbase Housings		
HALO	Catalog Number	Description
	Standard Housings	
	H7ICAT	6" Insulated Ceiling, AIR-TITE New Construction Housing
	H7RICAT	6" Insulated Ceiling, AIR-TITE Remodel Housing
	H7ICT	6" Insulated Ceiling, New Construction Housing
	H7RICT	6" Insulated Ceiling, Remodel Housing
	H7ICATNB	6" Insulated Ceiling, AIR-TITE New Construction Housing, No Socket Bracket
	H7ICTNB	6" Insulated Ceiling, New Construction Housing, No Socket Bracket
	H7T	6" Non-IC, New Construction Housing
	H7RT	6" Non-IC, Remodel Housing
	H7TNB	6" Non-IC, New Construction Housing, No Socket Bracket
	H7TCP	6" Non-IC, Chicago Plenum, New Construction/Remodel Housing
	H7UICT	6" Insulated Ceiling, Universal New Construction Housing
	H7UICAT	6" Insulated Ceiling, Universal, AIR-TITE, New Construction Housing
ALL-PRO	EI700AT	6" Insulated Ceiling, AIR-TITE New Construction Housing
	EI700RAT	6" Insulated Ceiling, AIR-TITE Remodel Housing
	EI700	6" Insulated Ceiling, New Construction Housing
	EI700R	6" Insulated Ceiling, Remodel Housing
	EI700ATNB	6" Insulated Ceiling, AIR-TITE New Construction Housing, No Socket Bracket
	EI700NB	6" Insulated Ceiling, New Construction Housing, No Socket Bracket
	EI700U	6" Insulated Ceiling, Universal New Construction Housing
	EI700UAT	6" Insulated Ceiling, Universal, AIR-TITE, New Construction Housing
	ET700	6" Non-IC, New Construction Housing
	ET700R	6" Non-IC, Remodel Housing

HOUSING – TRIM COMPATIBILITY - continued

HALO and All-Pro - Incandescent E26 Screwbase Housings - continued		
HALO	Catalog Number	Description
	Shallow Housings	
	H27ICAT	6" Shallow, Insulated Ceiling, AIR-TITE New Construction (use with 691X, 694X, 696X trims only)
	H27RICAT	6" Shallow, Insulated Ceiling, AIR-TITE Remodel Housing (use with 691X, 694X, 696X trims only)
	H27ICT	6" Shallow, Insulated Ceiling, New Construction Housing (use with 691X, 694X, 696X trims only)
	H27RICT	6" Shallow, Insulated Ceiling, Remodel Housing (use with 691X, 694X, 696X trims only)
	H27T	6" Shallow, Non-IC, New Construction Housing (use with 691X, 694X, 696X trims only)
	H27RT	6" Shallow, Non-IC, Remodel Housing (use with 691X, 694X, 696X trims only)
ALL-PRO	EI2700AT	6" Shallow, Insulated Ceiling, AIR-TITE New Construction (use with 691X, 694X, 696X trims only)
	EI2700	6" Shallow, Insulated Ceiling, New Construction Housing (use with 691X, 694X, 696X trims only)
	EI2700R	6" Shallow, Insulated Ceiling, AIR-TITE Remodel Housing (use with 691X, 694X, 696X trims only)
	ET2700	6" Shallow, Non-IC, New Construction Housing (use with 691X, 694X, 696X trims only)
	ET2700R	6" Shallow, Non-IC, Remodel Housing (use with 691X, 694X, 696X trims only)

Halo LED Retrofit Enclosures		
HALO	Catalog Number	Description
	ML7BXRFK	6" Retrofit Enclosure, Non-IC, BX Whip
	ML7E26RFK	6" Retrofit Enclosure, Non-IC, E26 Screw base Interface

5" Trims: 591X, 592X, 593X, 594X, 595X, 596X

(Note shallow housings for use with 591X, 594X, 596X trims only)

HALO - LED Housings with LED luminaire connector - high-efficacy compliant		
HALO	Catalog Number	Description
	H550ICAT	5" LED, Insulated Ceiling, AIR-TITE, New Construction Housing
	H550RICAT	5" LED, Insulated Ceiling, AIR-TITE, Remodel Housing

HALO and All-Pro - Incandescent E26 Screwbase Housings		
HALO	Catalog Number	Description
	Standard Housings	
	H5ICAT	5" Insulated Ceiling, AIR-TITE New Construction Housing
	H5RICAT	5" Insulated Ceiling, AIR-TITE Remodel Housing
	H5T	5" Non-IC, New Construction Housing
	H5RT	5" Non-IC, Remodel Housing
	H5TM	5" Non-IC, New Construction Housing (Canada)
ALL-PRO	EI500AT	5" Insulated Ceiling, AIR-TITE New Construction Housing
	EI500RAT	5" Insulated Ceiling, AIR-TITE Remodel Housing
	ET500	5" Non-IC, New Construction Housing
	ET500R	5" Non-IC, Remodel Housing
HALO	Shallow Housings	
	H25ICAT	5" Shallow, Insulated Ceiling, AIR-TITE New Construction (use with 591X, 594X, 596X trims only)

HOUSINGS - UL Classified for retrofit compatibility**6" Trims: 691X, 692X, 693X, 694X, 695X, 696X**

(Note shallow housings for use with 691X, 694X, 696X trims only)

Juno	Standard Housings
	IC22, IC22R, IC22W, IC22S, IC23, IC23W, TC2, TC2R, IC2
	Shallow Housings (use with 691X, 694X, 696X trims only)
	IC21, IC21R
Capri	Standard Housings
	CR1, PR1, QL1
	Shallow Housings (use with 691X, 694X, 696X trims only)
	R9ASIC/PS9RM
Elco	HL7ICA (EL7ICA)
Lithonia	Standard Housings
	LC6, L7X
	Shallow Housings (use with 691X, 694X, 696X trims only)
	L7XP
Thomas	PS1
Commercial Electric	C7ICA, H3
Progress	Standard Housing
	P87-AT † *
	Shallow Housing (use with 691X, 694X, 696X trims only)
	P86TG
Lightolier	1104ICS †*, 1104ICR †*

† Requires replacement of torsion springs with Friction Clips. Order Friction Clip Kit separately: ML56CLIP

* ML56CLIP is compatible with only baffle and reflector trims.

5" Trims: 591X, 596X


Juno	Standard Housings
	IC20, IC25S, IC25W, TC20

PHOTOMETRY

ML5606830-592SC	
Test Number	P92927
Light Module	600 Series, 80CRI
Trim	5" Aperture, Specular Clear Trim
Lumens	604.0
Efficacy	68.6 Lm/W
SC	1.08





CONE OF LIGHT			
D	FC	L	W
5.5	14.3	5.8	5.8
7	8.8	7.4	7.4
8	6.8	8.6	8.6
9	5.3	9.6	9.6
10	4.3	10.6	10.6
12	3.0	12.8	12.8



ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-30	312.76	51.80
0-40	466.79	77.30
0-60	597.43	98.90
0-90	603.99	100.0
90-180	0	0.0
0-180	603.99	100.0

ML5606830-595WW	
Test Number	P93087
Light Module	600 Series, 80CRI
Trim	5" Aperture, Wall Wash with Specular Clear Trim and Specular Clear Kick Reflector
Lumens	610.5
Efficacy	69.4 Lm/W
SC	1.08





ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-30	301.29	49.30
0-40	453.37	74.30
0-60	595.12	97.50
0-90	610.53	100.0
90-180	0	0.0
0-180	610.53	100.0

Legend

0-deg: --- Wall
90-deg: --- Side
180-deg: --- Room

ML5606830-594WB	
Test Number	P93055
Light Module	600 Series, 80CRI
Trim	5" Aperture, Directional Eyeball
Lumens	676.1
Efficacy	76.8 Lm/W
SC	1.21



30° HORIZONTAL PLANE					
D	FC	L	W	CB	
5.5	7.5	6.5	6.6	3.2	
7	4.6	8.3	8.4	4	
8	3.5	9.6	9.8	4.6	
9	2.8	10.7	11	5.2	
10	2.3	11.9	12.2	5.8	
12	1.6	14.3	14.6	6.9	

30° VERTICAL PLANE					
D	FC	L	W	CB	
5.5	4.836	6.2	7.2	9.5	
7	2.985	7.9	9.2	12.1	
8	2.286	9	10.4	13.9	
9	1.806	10	11.8	15.6	
10	1.463	11.1	13.2	17.3	
12	1.016	13.5	15.8	20.8	

ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-30	197.50	29.20
0-40	318.60	47.10
0-60	544.24	80.50
0-90	676.11	100.0
90-180	0	0.0
0-180	676.11	100.0

SINGLE UNIT FOOTCANDLES							
2.5' FROM WALL (Distance From Fixture Along Wall)							
DD	1'	2'	3'	4'	5'	6'	
1'	2.2	1.5	0.5	0.2	0	0	0
2'	7.9	5.8	2.6	0.9	0.2	0.1	0
3'	9.6	7.9	4.2	1.8	0.7	0.2	0.1
4'	6.9	6.2	4.4	2.4	1	0.5	0.2
5'	4.6	4.3	3.4	2.3	1.3	0.6	0.3
6'	3.1	2.9	2.5	1.9	1.3	0.8	0.4
7'	2.1	2.1	1.8	1.5	1.1	0.8	0.5
8'	1.5	1.5	1.4	1.2	0.9	0.7	0.5
9'	1.1	1.1	1	0.9	0.8	0.6	0.5
10'	0.9	0.8	0.8	0.7	0.6	0.5	0.4


MULTIPLE UNIT FOOTCANDLES						
2.5' FROM WALL (Distance From Fixture Along Wall)						
DD	--3'--	--4'--				
1'	2.4	1.9	2.4	2.3	1.1	2.3
2'	8.8	8.2	8.8	8.2	5.2	8.2
3'	11.4	11.9	11.4	10.3	8.3	10.3
4'	9.3	10.7	9.3	8	8.8	8
5'	6.9	7.8	6.9	5.9	6.8	5.9
6'	5	5.5	5	4.4	5	4.4
7'	3.6	3.9	3.6	3.3	3.7	3.3
8'	2.7	2.9	2.7	2.5	2.7	2.5
9'	2	2.1	2	1.9	2.1	1.9
10'	1.6	1.6	1.6	1.5	1.6	1.5

MULTIPLIER TABLE				
CCT Option	2700K	3000K	3500K	4000K
CCT Multiplier	1.00	1.00	1.05	1.04
Table based upon testing with 3000K color temperature, 80CRI.				
Multipliers may be used to determine relative lumen values with other color temperatures.				


Photometric tests are per IES measurement standards. Tests represent typical fixture performance. Field results may vary.

ML5606830-692SC


Test Number	P93151
Light Module	600 Series, 80CRI
Trim	6" Aperture, Specular Clear Trim
Lumens	623.2
Efficacy	70.8 Lm/W
SC	0.67



CONE OF LIGHT



CANDLEPOWER DISTRIBUTION




ZONAL LUMEN SUMMARY


Zone	Lumens	%Fixture
0-30	343.27	55.10
0-40	473.36	76.00
0-60	615.24	98.70
0-90	623.23	100.0
90-180	0	0.0
0-180	623.23	100.0

ML5606830-695WW

Test Number	P93327
Light Module	600 Series, 80CRI
Trim	6" Aperture, Wall Wash with Specular Clear Trim and Specular Clear Kick Reflector
Lumens	609.8
Efficacy	69.3 Lm/W
SC	0.74



CANDLEPOWER DISTRIBUTION



ZONAL LUMEN SUMMARY


Zone	Lumens	%Fixture
0-30	318.44	52.20
0-40	450.27	73.80
0-60	594.85	97.50
0-90	609.80	100.0
90-180	0	0.0
0-180	609.80	100.0

Legend


0-deg:	— — — — —	Wall
90-deg:	— — — — —	Side
180-deg:	— — — — —	Room

ML5606830-694WB


Test Number	P93295
Light Module	600 Series, 80CRI
Trim	6" Aperture, Directional Eyeball
Lumens	668.7
Efficacy	76.0 Lm/W
SC	1.22




CANDLEPOWER DISTRIBUTION

30°
HORIZONTAL
PLANE

D	FC	L	W	CB
5.5	7.4	6.6	6.6	3.2
7	4.6	8.3	8.6	4
8	3.5	9.6	9.8	4.6
9	2.8	10.8	11	5.2
10	2.2	12	12.2	5.8
12	1.6	14.4	14.6	6.9

30°
VERTICAL
PLANE

D	FC	L	W	CB
5.5	4.778	6.1	7.2	9.5
7	2.95	7.7	9.2	12.1
8	2.259	9	10.6	13.9
9	1.785	10.1	11.8	15.6
10	1.445	11.2	13.2	17.3
12	1.004	13.4	15.8	20.8



ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixture
0-30	194.63	29.10
0-40	314.35	47.00
0-60	537.23	80.30
0-90	668.66	100.0
90-180	0	0.0
0-180	668.66	100.0

SINGLE UNIT FOOTCANDLES

2.5' FROM WALL (Distance From Fixture Along Wall)							
DD	●	1'	2'	3'	4'	5'	6'
1'	1.8	1.1	0.4	0.1	0	0	0
2'	8	5.9	2.5	0.8	0.2	0.1	0
3'	8.6	7.1	4.1	1.8	0.7	0.2	0.1
4'	6.3	5.6	3.9	2.3	1.1	0.5	0.2
5'	4.5	4.1	3	2	1.2	0.7	0.3
6'	3.2	3	2.3	1.7	1.1	0.7	0.4
7'	2.4	2.2	1.8	1.4	1	0.7	0.5
8'	1.8	1.7	1.4	1.1	0.8	0.6	0.4
9'	1.4	1.3	1.1	0.9	0.7	0.5	0.4
10'	1.1	1	0.9	0.7	0.6	0.5	0.3

MULTIPLE UNIT FOOTCANDLES

2.5' FROM WALL (Distance From Fixture Along Wall)						
DD	--3'--		--4'--			
1'	1.9	1.5	1.9	1.8	0.9	1.8
2'	8.9	8.1	8.9	8.2	5.1	8.2
3'	10.4	11.3	10.4	9.2	8.3	9.2
4'	8.6	9.5	8.6	7.5	7.7	7.5
5'	6.5	7.2	6.5	5.7	6.1	5.7
6'	4.9	5.3	4.9	4.3	4.7	4.3
7'	3.7	4	3.7	3.4	3.6	3.4
8'	2.9	3.1	2.9	2.6	2.8	2.6
9'	2.3	2.4	2.3	2.1	2.2	2.1
10'	1.8	1.9	1.8	1.7	1.8	1.7

MULTIPLIER TABLE

CCT Option	2700K	3000K	3500K	4000K
CCT Multiplier	1.00	1.00	1.05	1.04
Table based upon testing with 3000K color temperature, 80CRI.				
Multipliers may be used to determine relative lumen values with other color temperatures.				

Photometric tests are per IES measurement standards. Tests represent typical fixture performance. Field results may vary.